


# EVERY DENNISON MARKETING SPECIFICATION

TOLERANCES IN. = .030 IN.  
MM = 0.7 mm



NOT TO SCALE

TENSILE STRENGTH: (LOOPED)	50 LBSF. / 22.7 KGF. MINIMUM PER MIL-S-23190.
OPERATING TEMP. RANGE:	-40°F (-40°C) TO 220°F (105°C)
MATERIAL:	IMPACT MODIFIED NYLON 6/6 PER ASTM D4066 - HEAT STABILIZED, BROWN
WEIGHT:	2.2 GRAMS/EACH
BUNDLE DIAMETER:	7/8" - 1-3/4"
MOUNTING:	8MM HOLE
APPLICATION TOOL:	12001 - HAND INSTALLATION TOOL 12500 - PNEUMATIC INSTALLATION TOOL
TOOL TENSION SETTING:	6-8
PACKAGED IN:	500/BAG, 10 BAGS/MASTER



FASTENER DIVISION  
FITCHBURG, MA 01420 U.S.A.  
TEL. 1-800-225-5913  
MA. 978-353-8157

DESCRIPTION:

M8 FIR TREE WITH STOP, BROWN

APPROVALS:

T.S.:

ENG'RG:

STOCK NO.

20086

REV.

B